AD-A257 703

2

TGAL-92-16

MULTITAPER CROSS-SPECTRAL ANALYSIS AND RELATED STUDIES OF NTS EXPLOSIONS

Indra N. Gupta
Peter Davis
Thomas W. McElfresh

Teledyne Geotech Alexandria Laboratories 314 Montgomery Street Alexandria, VA 22314-1581

OCTOBER 1992 SEMI-ANNUAL REPORT No. 2 (5 April 1992 - 23 August 1992) Approved for Public Release; Distribution Unlimited

Prepared for: UNITED STATES AIR FORCE AIR FORCE SYSTEM COMMAND PHILLIPS LABORATORY (PL) KIRTLAND AFB, NM 87117-6008

Monitored by:
DEFENSE ADVANCED RESEARCH PROJECTS AGENCY
NUCLEAR MONITORING RESEARCH OFFICE
3701 NORTH FAIRFAX DRIVE
ARLINGTON, VA 22203-1714



The views and conclusions contained in this report are those of the authors and should not be interpreted as representing the official policies, either expressed or implied, of the Defense Advanced Research Projects Agency or the U.S. Government.

405601 92-29352

92 11 12 126

REPORT DOCUMENTATION PAGE

Form Approved
OMB No. 0704-0188

Public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden. To Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA. 22202-4302, and to the Office of Management and Budget, Paperwork Reduction Project (0704-0188), Washington, DC. 20503.

A ACCRECY LICE ONLY (Land Market	I A DECORAT CATE	12 DEPOST TYPE AND DATES COVERED
1. AGENCY USE ONLY (Leave blank)	2. REPORT DATE 29 October 1992	3. REPORT TYPE AND DATES COVERED Technical Report, 5 Apr 1992 - 23 Aug 199
4. TITLE AND SUBTITLE	27 0010001 1772	5. FUNDING NUMBERS
Multitaper Cross-Spectral A	naturis and Related Stud	
-	liarysis and reduce orde	ines of 1V15
Explosions		Contract F29601-91-C-DB0
6. AUTHOR(S)		Contract 1.525001-51-C-DD0
I. N. Gupta, J. P. Davis, and		
7. PERFORMING ORGANIZATION NAME((S) AND ADDRESS(ES)	8. PERFORMING ORGANIZATION REPORT NUMBER
Teledyne Geotech		REPURT NUMBER
314 Montgomery Street		TC 41 00 16
Alexandria, VA 22314-1581		TGAL-92-16
Alcanula, VA 22314-1301		
9. SPONSORING/MONITORING AGENCY	NAME(S) AND ADDRESS(ES)	10. SPONSORING / MONITORING
Phillips Laboratory (PL/PKR Kirtland AFB, NM 87117-53	7 3 // IL NOMB HAIM	fax Drive, #717
11. SUPPLEMENTARY NOTES		
12a. DISTRIBUTION / AVAILABILITY STAT	EMENT	12b. DISTRIBUTION CODE
Approved for Public Release;	; Distribution Unlimited	
13. ABSTRACT (Maximum 200 words) During this report period	1 coftware for determin	ing the delay time between two ways

During this report period, software for determining the delay time between two waveforms was further developed and tested on real data. The main improvement was use of the multitaper method of spectral analysis which has been shown to yield better results than standard single-taper procedures. This procedure constitutes a significant improvement over all previous studies of cross-spectral analysis based on the use of a single taper. An application to closely-located Yucca Flat explosions recorded at four stations showed significant improvement over single-taper results. Intersource coherence for Pn was found to be significantly greater when the two sources lay along the direction of wave propagation than when perpendicular to it. Mean velocities along the four source-receiver paths were found to be stable and significantly different, suggesting that propagation velocities may vary considerably from one path to another. It seems therefore that at least a part of the observed location errors are due to the assumption of a uniform path-independent velocity model in the computation of location. Analysis of data from two closely located explosions suggests that the cross-spectral method may also be used to determine very small differences (of the order of 1%) between propagation velocities of regional phases.

14. SUBJECT TERMS	15. NUMBER OF PAGES		
Multitaper, Relative Loc	41		
Inter-Source Coherence,	16. PRICE CODE		
17. SECURITY CLASSIFICATION OF REPORT	18. SECURITY CLASSIFICATION OF THIS PAGE	19. SECURITY CLASSIFICATION OF ABSTRACT	20. LIMITATION OF ABSTRACT
Unclassified	Unclassified	Unclassified	UL

1. SUMMARY

During this report period, software for determining the delay time between two waveforms was further developed and tested on real data. The main improvement was use of the multitaper method of spectral analysis which has been shown to yield better results than standard single-taper procedures. This procedure constitutes a significant improvement over all previous studies of cross-spectral analysis based on the use of a single taper. An application to closely-located Yucca Flat explosions recorded at four stations showed significant improvement over single-taper results. Inter-source coherence for Pn was found to be significantly greater when the two sources lay along the direction of wave propagation than when perpendicular to it. Mean velocities along the four source-receiver paths were found to be stable and significantly different, suggesting that propagation velocities may vary considerably from one path to another. It seems therefore that at least a part of the observed location errors are due to the assumption of a uniform path-independent velocity model in the computation of location. Analysis of data from two closely located explosions suggests that the cross-spectral method may also be used to determine very small differences (of the order of 1%) between propagation velocities of regional phases.

NTIS CRA&I
DTIC TAB
Unannounced
Justification

By
Distribution /

Availability Codes
Avail and / or

Special

Accesion For

Dist

DIEC OF ALBERT IN PRICEED 1

(THIS PAGE INTENTIONALLY LEFT BLANK)

TABLE OF CONTENTS

		Page
1.	SUMMARY	iii
2.	INTRODUCTION	1
3.	CROSS-SPECTRAL ANALYSIS WITH MULTITAPER	2
4.	COMPARISON OF DATA FROM TWO CLOSELY LOCATED SHOTS	20
5.	CONCLUSIONS	24
6.	ACKNOWLEDGMENTS	25
7.	REFERENCES	26
	DISTRIBUTION LIST	27

(THIS PAGE INTENTIONALLY LEFT BLANK)

2. INTRODUCTION

Location relative to a known reference event is often more useful and precise than absolute event location. The use of relative location compensates for most of the errors arising from path effects. Such location requires relative arrival times for pairs of events observed at common stations, which can be obtained with high precision for similar events by waveform cross-correlation. This estimate of the relative time based on the full waveform is generally more precise than that based on rather subjective picks of the initial phase arrival. Conventional cross-correlation slides one waveform past another, and the lag with the optimum correlation coefficient is taken as the relative time. However, the cross-spectral analysis method can yield relative delay times with resolution up to an order magnitude better than the seismogram sampling interval.

Most of the effort during the report period was devoted to developing the software for multitaper. An application to the available data from Yucca Flat explosions demonstrated significant improvement in relative locations. The cross-spectrum method was also applied to regional data from two closely located Pahute Mesa, NTS explosions recorded at two common stations. Preliminary results suggest that the analysis can detect very small differences (of the order of 1%) in the propagation velocities of regional phases generated by the two shots. A knowledge of these differences may be useful in a comparison of the near-source properties of closely located explosions.

3. CROSS-SPECTRAL ANALYSIS WITH MULTITAPER

Single taper cross-spectral analysis of regional data from Yucca Flat explosions with precisely known locations provided relative locations that were accurate to within about 1 km. However, locations based on arrival times determined by alignment of the first peaks were found to be somewhat better (Gupta and Davis, 1992). A possible reason for this disappointing performance was suspected to be the use of a cosine taper on rather short signal windows. We therefore applied the multitaper method of spectral analysis which has been shown to yield better results than standard single-taper procedures (Park et al., 1987; Zhu et al., 1989).

We employed the multitaper method, based on a family of tapers which are resistant to spectral leakage, by mainly following the procedure described by Park et al. (1987) and Vernon et al. (1991). A set of k tapers $v_n^k(n,w)$ are generated which are functions of the time series length n and the specified inner bandwidth w. The tapers are the eigenvectors of the Toeplitz matrix with associated eigenvalues λ_k . Following Park et al. (1987), w was selected to be 4, and only those tapers with λ_k greater than 0.9 were used. With these two restrictions, k was found to be equal to 7, independent of the number of points in the signal window.

Consider two signals A and B represented by the time series $f_a(t)$ and $f_b(t)$, respectively. The signals are windowed (e.g. 64 or 128 samples of data), calibrated, demeaned, and detrended, providing the signals $X_a(n)$ and $X_b(n)$, respectively, where n is the number of samples in the selected window. Let $Y_a^k(N)$ and $Y_b^k(N)$ represent the Fourier transforms of $v_n^k X_a(n)$ and $v_n^k X_b(n)$, where $N = \frac{n}{2} + 1$, respectively.

An adaptive spectral estimate of $f_a(t)$, \hat{S}_a is formed by

$$\hat{S}_{a} = \frac{\sum_{k} |d_{a}^{k}(N)| Y_{a}^{k}(N)|^{2}}{\sum_{k} |d_{a}^{k}(N)|^{2}}$$
(1)

where the weights d_a^k , which depend on frequency (N) and on the taper order k, are chosen to reduce bias from spectral leakage. An initial spectral estimate is made by assuming

$$\hat{S}_{a} = \frac{|Y_{a}^{1}|^{2} + |Y_{a}^{2}|^{2}}{2} \tag{2}$$

The first guess for weights is then made by

$$d_{a}^{k}(N) = \frac{\sqrt{\lambda_{k}} \, \hat{S}_{a}}{\lambda_{k} \, \hat{S}_{a} + (1 - \lambda_{k}) \sum_{i=1}^{n} [X_{a}(i)]^{2}}$$
(3)

A new spectral estimate of \hat{S}_a is made by inserting the weights from equation (3) into equation (1) and using this new value into equation (3) to compute the corresponding new weights. This process is repeated until the difference between two successive \hat{S}_a is less than 0.0001. Once the weights have been determined, the multitaper cross-spectrum is computed from:

$$Y_{ab} = \frac{\sum_{k} (\lambda_{k})^{-1} \sum_{k} \lambda_{k} d_{a}^{k}(N) Y_{a}^{k}(N) d_{b}^{k}(N) Y_{b}^{k*}(N)}{k \left[\sum_{k} (d_{a}^{k}(N)^{2})^{1/2} \left[\sum_{k} (d_{b}^{k}(N)^{2})^{1/2}\right]^{1/2}}$$
(4)

where * indicates the complex conjugate. If Yab is expressed as

$$Y_{ab}(N) = Re(N) + i Im(N), \tag{5}$$

the phase spectrum $\phi(N)$ is

$$\phi(N) = \tan^{-1} \frac{\text{Im}(N)}{\text{Re}(N)} \tag{6}$$

If the two seismograms are identical in shape but have different amplitudes and are shifted in time by τ , then

$$f_b(t) = k f_a(t+\tau), \tag{7}$$

and by the application of the shift theorem, the phase spectrum becomes

$$\phi(N) = 2 \pi N \tau \tag{8}$$

Thus the delay time τ can be obtained simply by fitting a straight line through the phase of the cross-spectrum with zero intercept. In fitting this slope, the values are weighted based on the coherence γ_{ab} :

$$\gamma_{ab}^2 = \frac{|Y_{ab}|^2}{Y_{aa} Y_{bb}}$$
 (9)

The weighting factor, W(N) in the linear fit is based on the Hannon-Thomson processor (Knapp and Carter, 1976), i. e.

$$W(N) = \frac{\gamma_{ab}^{2}(N)}{1 - \gamma_{ab}^{2}(N)}$$
 (10)

The slope of the line has a continuum of possible values, rather than discrete values, with the result that estimates of delay time for highly coherent pairs can actually be an order of magnitude more precise than the sample rate. This technique has been applied successfully to local sequences of earthquakes with impressively precise locations (Ito, 1985; Fremont and Malone, 1987).

Regional data from six closely spaced underground nuclear explosions at the Nevada Test Site (NTS), recorded at the four broadband digital stations, ELK, KNB, LAC, and MNV (Table 1 and Figure 1), have been analyzed to determine how the cross-spectral method may best be used to improve relative locations. For these explosions, with precisely known locations, the near-source geological and geophysical properties are also known so that the influence of parameters such as shot depth and geological environment can also be investigated. Software for determining the delay time between two waveforms has been developed and tested. The relative arrival times between two events recorded at a common station are determined with a precision of 0.001 sec. As an example, results from the vertical component




Figure 1. Map of six Yucca Flat explosions used in the study. Azimuthal directions and distances from BASEBALL to the four recording stations are indicated.

ELK records of the Yucca Flat explosions BASEBALL and PALIZA are shown in Figure 2. The digital data are sampled at 42 samples/sec and the signal window is 64 points (about 1.5 sec). Figure 2 (bottom) shows the input waveforms which may be selected to be of any desired duration. The signal window over which a cosine taper applies is also variable. The top plot shows the phase of the cross-spectrum varying between $-\pi$ and $+\pi$ whereas the lower plot shows the coherency, varying between 0 and 1, derived by using a bandwidth of 2.0 Hz. The delay time of 0.0477 (0.0473) sec is simply the slope of the phase of the cross-spectrum over the specified range of 0.5-5.0 Hz and is obtained by fitting a slope through 0, using a weighting scheme based on coherence of the cross-spectrum (equation 10); the quantity within parentheses denotes one standard deviation.

TABLE 1
6 YUCCA FLAT EXPLOSIONS USED IN STUDY

No.	DATE	NAME	m _b	P-WAVE VEL (KM/S)	SHOT DEPTH (KM)	DEPTH OF WT (KM)
1	06 Sep 1979	HEARTS (B)	5.892	1.763	0.6400	0.5070
2	14 Nov 1980	DAUPHIN (A)	4.554	1.420	0.3200	0.5800
3	15 Jan 1981	BASEBALL (B)	5.725	1.970	0.5639	0.5120
4	01 Oct 1981	PALIZA (A)	5.115	1.497	0.4724	0.5300
5	11 Nov 1981	TILCI (A)	5.035	1.600	0.4450	0.4940
6	12 Nov 1981	ROUSANNE (B)	5.458	1.580	0.5182	0.4950

Note: B and A denote shots below and above the water table, respectively.

Figure 3 shows results of cross-spectral analysis when the signal window is doubled to 128 points. A comparison with Figure 2 shows a decrease in the average coherency and an increase in the delay time. Results when the cosine tapers in Figures 2 and 3 are replaced by multitaper are shown in Figures 4 and 5, respectively. Note the significant improvement in




Figure 2. Cross-spectral analysis for measuring delay times based on use of the cosine taper. The two input waveforms at ELK (bottom), each 64 points long, provide the phase of the cross-spectrum (top) and coherence based on bandwidth of 2.0 Hz for frequencies up to 10 Hz. Mean slope of the phase spectrum, averaged over the indicated frequency range of 0.5-5.0 Hz, provides the delay time used to obtain the corrected arrival time for PALIZA.




Figure 3. Similar to Figure 2 for signal windows of 128 points.




Figure 4. Similar to Figure 2 based on use of the multitaper (seven tapers).




Figure 5. Similar to Figure 2 based on use of the multitaper and signal windows of 128 points.

the determination of delay times as indicated by the improved fits of mean slope and the reduced values of standard deviation.

Assuming BASEBALL to be the reference shot with known location and its first peak at each station as the reference time, cross-spectral analysis was carried out to obtain the corrected arrival times (such as those indicated on Figures 2, 3, 4, and 5) for each explosion recorded at the four stations. Results based on use of the cosine taper and signal windows of 128 points were first determined. For each explosion, the four arrival times are used as input to the LOCATE feature of the Analyst Review Station (ARS) to obtain the epicentral location and the origin time. The arrival times (without any delay correction) for BASEBALL recorded at the four stations are also used to compute the corresponding ARS location. The ARS computed locations and the actual (known) locations of six explosions are shown in Figure 6. The ARS computed locations for the five shots (paired with BASEBALL) are shifted by the amount of shift between the ARS computed and actual locations of BASEBALL. A comparison of the shifted locations of each of the five shots with its actual location provides the location error associated with each shot (Figure 6). The mean location error is only 1.32 (0.61) km. Cross spectral analysis based on the use of longer (256 points) windows was also carried out for the same six explosions. Using a bandwidth of 1.0 Hz for deriving coherency and a frequency range of 0.5-5.0 Hz for computing the delay time, the location results were found to be very similar to those in Figure 6 in both the magnitude and azimuthal direction of the location errors; the mean location error was 1.22 (0.61) km.

Locations based on the use of arrival times determined by simple alignment of the first peaks at common stations are shown in Figure 7. A comparison with locations derived by using the cross-spectral analysis (Figure 6) shows significant improvement, especially for the




Figure 6. Location results for six Yucca Flat explosions based on arrival times derived from cross-spectral analysis using the cosine taper and signal windows of 128 points. Actual locations, ARS computed locations, and locations with shift based on BASEBALL are shown; the five lines indicate the error between the actual and computed locations. Mean location error is 1.318 (0.614) km.




Figure 7. Similar to Figure 6 but derived from simple alignment of the first peaks of all explosions recorded at the four recording stations. Mean location error is 1.017 (0.218) km.

two shots PALIZA and TILCI. The mean location error is only 1.017 (0.218) km. Possible reasons for the smaller accuracy of the cross-spectral analysis are the spectral leakage and variability for the estimates expected when cosine taper is used on rather short time series (Vernon et al., 1991).

Location results based on use of the multitaper and signal windows of 64 points are shown in Figure 8. There is significant improvement compared to the results with cosine taper (Figure 6); the mean location error is 1.010 (0.221) km. These results appear to be impressive if one considers the large epicentral distances (about 200 km to 400 km) and the complex geology of the Nevada test site.

Analysis of regional data from Yucca Flat explosions also provides valuable information regarding inter-source coherence of closely located explosions recorded at common stations. A comparison of the coherency plots in Figures 2 and 3 or Figures 4 and 5 indicate that the shorter signal windows of Pn have significantly better coherency over a much larger range of frequency than the longer windows. This implies that the first arrivals in Pn are considerably more similar than the later arriving phases, perhaps due to greater contamination by laterarriving scattered energy. Furthermore, inter-source coherence for Pn appears to be significantly greater when the two sources lie along the direction of wave propagation than when perpendicular to it. This is illustrated by comparison of coherence at ELK and KNB for two pairs of explosions BASEBALL and ROUSANNE (Figure 9) and BASEBALL and PALIZA (Figure 10). These results were based on use of the multitaper and signal windows of 128 points. For BASEBALL and ROUSANNE, ELK and KNB are nearly along and perpendicular to the direction of wave propagation, respectively. On the other hand, for BASEBALL and PALIZA, ELK and KNB approximate directions perpendicular to and along the




Figure 8. Similar to Figure 6 but derived from cross-spectral analysis based on use of the multitaper and signal windows of 64 points. Mean location error is 1.010 (0.221) km.




Figure 9. Waveform and coherency plots for BASEBALL and ROUSANNE recorded at ELK and KNB showing the inter-source coherency for Pn (over the frequency range of 0.1-3.0 Hz) to be larger when the two sources lie nearly along the direction of wave propagation than when approximately perpendicular to it.




Figure 10. Waveform and coherency plots for BASEBALL and PALIZA recorded at ELK and KNB, again showing the inter-source coherency for Pn (over the frequency range of 0.1-3.0 Hz) to be larger when the two sources lie nearly along the direction of wave propagation than when approximately perpendicular to it.

wave propagation. These results, based on use of the multitaper and signal windows of 128 points, are similar to the inter-sensor coherence of regional phases generally observed to be greater along the radial direction than along the transverse direction. An attempt will be made to exploit these coherency differences to improve locations. Analysis of the Lg phase showed the inter-source coherence to be significantly smaller than for Pn, again similar to the observed inter-sensor coherence results for Lg and Pn. Also, coherency appeared to vary significantly from one station to another.

In order to understand what causes the discrepancy between the actual locations and those computed from observations of Pn from the Yucca Flat explosions, we examined the lateral variations in the Pn velocity under the test site. Pn arrival times from closely spaced explosions can be used to estimate average velocities to various stations if the spatial locations of the explosions are precisely known and data from at least two shots are available.

Consider a number of closely located sources, S_i recorded at a number of well-separated receivers, R_j . Let the average P-wave velocities from the limited source region to the relatively distant receivers be α_j . If r_{ij} represents the distance from source S_i to the receiver R_j and z_i are the origin times of the various sources, then the P-wave arrival times, T_{ij} are given by

$$T_{ij} = \frac{r_{ij}}{\alpha_j} + z_i \tag{11}$$

Having data from two or more sources at two or more receivers, we can solve for α_j by using the method of least squares.

Using Pn arrival times, based on alignment of the first peaks, from six explosions (Table 1) recorded at the four stations, the mean velocities to the four stations ELK, KNB, LAC, and

MNV were determined to be 7.051 (0.006), 6.636 (0.007), 6.767 (0.007), and 6.469 (0.008), respectively. The quantities within parentheses, denoting one standard deviation of the mean, are remarkably small so that the velocity differences are significant and outside the margin of error. The large differences in mean velocities (maximum about 9%) along the four source-receiver paths suggest that propagation velocities may vary considerably from one path to another. Moreover, our results indicate velocities along the north-south direction to be somewhat larger than those along the east-west direction, in general agreement with the tectonics of the region and the velocity measurements of Harmsen (1992). It seems therefore that at least a part of the observed location errors are due to the assumption of a uniform path-independent velocity model.

4. COMPARISON OF DATA FROM 1 WO CLOSELY LOCATED SHOTS

Cross-spectrum analysis has been used to provide a high-precision method for measuring temporal velocity changes in the earth's crust (Poupinet et al., 1987). The method compares the scattered wave portions, or coda, of two highly similar waveforms, generated by a pair of nearly identical sources (called doublets), recorded at the same receiver at different times. By analyzing progressive relative phase delays between the two doublet signals as a function of elapsed time, velocity changes on the order of 0.01% could be measured. The high precision of the doublet method is possible because coda waves from colocated sources will sample the same regions and generally follow paths that increase in length with elapsed time. Thus a small decrease in velocity occurring within the sampled region during the time period between the doublet origin times will produce a relative delay that increases with elapsed time over some portion of the scattered waves. If the velocity change is pervasive, the relative delay may increase linearly over the entire coda. This trend of increasing delay is easier to detect and measure than an isolated delay based on a single arrival. Using active, repeatable sources instead of natural earthquakes, Roberts et al. (1992) used the doublet method for measuring small velocity and attenuation changes in solids.

The Pahute Mesa explosions BUTEO (12 May 1965, shot depth 696 m, yield 0.7 kt) and DURYEA (14 April 1966, shot depth 544 m, yield 65 kt) were closely located (probably in the same hole) and generated similar records at two common LRSM stations, KN-UT and MN-NV at epicentral distances of 321 and 201 km, respectively (Blandford, 1976). Using 20 samples/sec data at KN-UT, time delays were measured for overlapping 128-point windows incremented by 1 sec. A plot of the mean slopes of the phase spectra of each window, averaged over the frequency range of 0.5-2.0 Hz, versus the elapsed time is shown in Figure 11a.




Figure 11. Comparison of the LRSM station KN-UT records of DURYEA and BUTEO showing (a) delay time, (b) coherency, and (c) differential bandpassed (0.5-2.0 Hz) log-rms amplitude versus time starting about 2 sec before the onset of Pn. Results are based on overlapping windows of length 6.4 sec for (a) and (b) and 10 sec for (c) with incremental shift of 1.0 sec for (a) and (b) and 0.5 sec for (c). Bandpassed waveforms of the two explosions are shown at bottom.

The corresponding coherency is plotted in Figure 11b. In Figure 11a, the mean slope, averaged over the first 50 sec of data, appears to suggest a medium velocity differential of about 0.6%. Bandpassed (0.5-2.0 Hz) log-rms amplitudes, based on overlapping windows of length 6.4 sec and incremental shift of 0.5 sec, were also obtained for the two shots (see Gupta and Wagner, 1992 for more details). Figure 11c shows the differential (DURYEA - BUTEO) log-rms amplitude versus time starting about 2 sec before the onset of Pn. Bandpassed waveforms of the two explosions are shown at bottom.

Results of similar processing of data from the same two explosions recorded at MN-NV are shown in Figure 12. The mean slope in Figure 12a, averaged over the first 25 sec of data, suggests a medium velocity differential of about 1.0%. These results, although preliminary and subject to revision in view of the coherency declining rapidly with time, suggest that the cross-spectral analysis can be used to determine very small differences between similar waveforms of two closely spaced explosions.




Figure 12. Similar to Figure 11 for the recording LRSM station MN-NV.

5. CONCLUSIONS

A comparison of relative locations based on application of a single taper versus the multitaper to cross-spectral analysis of regional data from Yucca Flat explosions shows significant improvement when the multitaper is used. An accuracy of about 1 km has been achieved; an impressive result if one considers the large epicentral distances (about 240 and 410 km) and the complex geology around the Nevada Test Site. Inter-source coherence for Pn is found to be significantly greater when the two sources lie along the direction of wave propagation than when perpendicular to it. Mean velocities along paths from the Yucca Flat source region to four stations are found to be stable and significantly different, suggesting that propagation velocities may vary considerably from one path to another. This means that at least a part of the observed location errors are due to the assumption of a uniform path-independent velocity model. Analysis of regional data from two closely located shots suggests that the cross-spectral method may also be used to determine very small differences (of the order of 1%) between propagation velocities of regional phases from pairs of closely spaced explosions.

6. ACKNOWLEDGMENTS

This research was funded by the Nuclear Monitoring Research Office of the Defense Advanced Research Projects Agency under Contract F29601-91-C-DB07. The views and conclusions contained in this paper are those of the authors and should not be interpreted as necessarily representing the official policies, either expressed or implied, of the Defense Advanced Research Projects Agency or the U. S. Government.

7. REFERENCES

- Blandford, R. R. (1976). Experimental determination of scaling laws for contained and cratering explosions, SDAC-TR-76-3, Teledyne Geotech, Alexandria, Virginia.
- Frankel, A. and R. W. Clayton (1986). Finite difference simulations of seismic scattering: implications for the propagation of short-period seismic waves in the crust and models of crustal heterogeneity, J. Geophys. Res. 91, 6465-6489.
- Fremont, M. J. and S. D. Malone (1987). High precision relative locations of earthquakes at Mount St. Helens, Washington, J. Geophys. Res. 92, 10223-10236.
- Gupta, I. N. and J. P. Davis (1992). High-precision relative event location with cross-spectral analysis and related studies, *Proc. 14th Annual PL/DARPA Seismic Research Symposium*, 146-152.
- Gupta, I. N. and R. A. Wagner (1992). Evidence for Rg-to-P scattering in teleseismic P-coda of East Kazakh explosions, *Bull. Seism. Soc. Am.* 82, (in press).
- Harmsen, S. C. (1992). Regional-scale velocity anisotropy inferred from Nevada Test Site nuclear test P-arrivals, Seismol. Res. Lett. 63, 39 (abstract).
- Ito, A. (1985). High resolution relative hypocenters of similar earthquakes by cross-spectral analysis method, J. Phys. Earth 33, 279-294.
- Knapp, C. H., and G. C. Carter (1976). The generalized method for estimation of time delay, *IEEE Transactions on Acoustics, Speech, and Signal Processing* 24, 320-327.
- Park, J., C. R. Lindberg, and F. L. Vernon information (1987). Multitaper spectral analysis of high-frequency seismograms, J. Geophys. Res. 92, 12675-12684.
- Poupinet, G., W. L. Ellsworth, and J. Frechet (1984). Monitoring velocity variations in the crust using earthquake doublets: an application to the Calaveras Fault, California, J. Geophys. Res. 89, 5719-5731.
- Roberts, P. M., W. S. Phillips, and M. C. Fehler (1992). Development of the active doublet method for measuring small velocity and attenuation changes in solids, *J. Acoust. Soc. Am. 91*, 3291-3302.
- Thomson, D. J. (1982). Spectrum estimation and harmonic analysis, *Proc. IEEE 70*, 1055-1096.
- Vernon, F. L., J. Fletcher, L. Carroll, A. Chave, and E. Sembera (1991). Coherence of seismic body waves from local events as measured by a small-aperture array, J. Geophys. Res. 96, 11981-11996.
- Zhu, T., K. Y. Chun, and G. F. West (1989). High-frequency P-wave attenuation determination using multiple-window spectral analysis method, *Bull. Seism. Soc. Am.* 79, 1054-1069.

NON-GOVERNMENT_CONTRACTORS

Prof. Thomas Ahrens Seismological Lab, 252-21 Div. of Geol. & Planetary Sciences California Institute of Technology Pasadena, CA 91125

Dr. Thomas C. Bache, Jr. Dr. Thomas J. Serena, Jr. Science Applications Int'l Corp. 10260 Campus Point Drive San Diego, CA 92121 (2 copies)

Dr. Peter Basham Dr. Robert North Earth Physics Branch Geological Survey of Canada 1 Observatory Crescent Ottawa, Ontario, CANADA KIA OY3

Dr. Douglas R. Baumgardt Dr. Zoltan Der ENSCO, Inc. 5400 Port Royal Road Springfield, VA 22151-2388

Prof. Jonathan Berger IGPP, A-025 Scripps Institution of Oceanography University of California, San Diego La Jolla, CA 92093

Dr. G. A. Bollinger Department of Geological Sciences Virginia Polytechnic Institute 21044 Derring Hall Blacksburg, VA 24061

The Librarian Dr. Jerry Carter Dr. Stephen Bratt Center for Seismic Studies 1300 North 17th Street, Suite 1450 Arlington, VA 22209-2308 (raigo EL

Michael Browne Teledyne Geotech 3401 Shiloh Road Garland, TX 75041

Dr. Lawrence J. Burdick Woodward-Clyde Consultants 566 El Dorado Street Pasadena, CA 91109-3245

Dr. Theodore Cherry Science Horizons, Inc. 710 Encinitas Blvd., Suite 200 Encinitas, CA 92024 (2 copies)

Dr. Kin Yip Chun Geophysics Division Physics Department University of Toronto Ontario, CANADA M5S 1A7

Dr. Paul M. Davis Dept. Earth & Space Sciences University of California (UCLA) Los Angeles, CA 90024

Prof. Steven Day Department of Geological Sciences San Diego State University San Diego, CA 92182

Ms. Eva Johannisson Senior Research Officer National Defense Research Institute P.O. Box 27322 S-102 54 Stockholm, SWEDEN

Dr. Mark D. Fisk Mission Research Corporation 735 State Street P.O. Drawer 719 Santa Barbara, CA 93102

Prof. Stanley Flatte Applied Sciences Building University of California Santa Cruz, CA 95064

Dr. Roger Fritzel Pacific Sierra Research 1401 Wilson Blvd., Suite 1100 Arlington, VA 22209

Dr. Holly K. Given Inst. Geophys. & Planet. Phys. Scripps Inst. Oceanography (A-025) University of California-San Diego La Jolla, CA 92093

Prof. Hans-Peter Harjes Institute for Geophysik Ruhr University/Bochum P.O. Box 102148 4630 Bochum 1, FRG

Prof. Donald V. Helmberger Seismological Laboratory Div. of Geol. & Planetary Sciences California Institute of Technology Pasadena, CA 91125

Prof. Eugene Herrin Prof. Brian Stump Inst. for the Study of Earth and Man Dr. Susan Schwartz Geophysical Laboratory Southern Methodist University Dallas, TX 75275

Prof. Bryan Isacks Prof. Muawia Barazangi Cornell University Department of Goological Sciences SNEE Hall Ithaca, NY 14850

Prof. Lane R. Johnson Prof. Thomas V. McEvilly Seismographic Station University of California Berkeley, CA 94720

Robert C. Kemerait ENSCO, Inc. 445 Pineda Court Melbourne, FL 32940

TO

Prof. Brian L. N. Kennett Research School of Earth Sciences Institute of Advanced Studies G.P.O. Box 4 Canberra 2601, AUSTRALIA

Dr. Richard LaCoss MIT-Lincoln Laboratory M-200B P.O. Box 73 Lexington, MA 02173-0073

Prof. Fred K. Lamb Univ. of Illinois Department of Physics 1110 West Green Street Urbana, IL 61801

Prof. Charles A. Langston Geosciences Department 403 Deike Building The Pennsylvania State University University Park, PA 16802

Prof. Thorne Lay Institute of Tectonics Earth Science Board University of California, Santa Cruz Santa Cruz, CA 95064

Prof. Arthur Lerner-Lam Prof. Paul Richards Prof. C. B. Scholz Lamont-Doherty Geol.Observatory of Columbia University Palisades, NY 10964

Dr. Manfred Henger Fed. Inst. for Geosci. & Nat'l Res. Postfach 510153 D-3000 Hanover 51, FRG

Dr. Peter Marshall Procurement Executive Ministry of Defense Blacknest, Brimpton Reading FG7-4RS, UNITED KINGDOM

Dr. Randolph Martin, III New England Research, Inc. 76 Olcott Drive White River Junction, VT 05001

Dr. Bernard Massinon Societe Radiomana 27 rue Claude Bernard 75005 Paris, FRANCE (2 copies)

Dr. Gary McCartor Prof. Henry L. Gray Department of Physics Southern Mathodist University Dallas, TX 75275

Dr. Keith L. McLaughlin S-CUBED 9.0. Box 1620 La Jolla, CA 92038-1620

Dr. Pierre Mecheler Societe Radiomana 27 rue Claude Bernard 75005 Paris, FRANCE

Prof. Bernard Minster Prof. John Orcutt Dr. Holly Given IGPP, A-025 Scripps Institute of Oceanography University of California, San Diego La Jolla, CA 92093

Prof. Brian J. Mitchell Dr. Robert Herzmann Dept of Earth & Atmospheric Sciences Dr. Stewart W. Smith St. Louis University St. Louis, MO 63156

Mr. Jack Murphy S-CUBED 11800 Sunrise Valley Drive Suite 1212 Reston, VA 22091 (2 copies)

Dr. Jay J. Pulli Radix Systems, Inc. 2 Taft Court, Suite 203 Rockville, HD 20850

Dr. Prode Ringdal Dr. Svein Mykkeltveit NTNF/NORSAR P.O. Box 51 N-2007 Kjeller, NORWAY (2 copies)

Dr. Wilmer Rivers Teledyne Geotech 314 Montgomery Street Alexandria, VA 22314 (2 copies)

Dr. Richard Sailor TASC, Inc. 55 Walkers Brook Drive Reading, MA 01867

Prof. Charles G. Sammis Prof. Kei Aki Center for Earth Sciences University of Southern California University Park Los Angeles, CA 90089-0741

Prof. David G. Simpson Lamont-Doherty Geological Observatory of Columbia University Palisades, NY 10964

Geophysics AK-50 University of Washington Scattle, KA 98195

Prof. Clifford Thurber
Prof. Robert P. Meyer
University of Wisconsin-Madison
Department of Geology & Geophysics
1215 West Dayton Street
Madison, WS 53706

Prof. M. Nafi Toksom
Prof. Anton Dainty
Earth Resources Lab
Mass. Institute of Technology
42 Carleton Street
Cambridge, MA 02142

Prof. Terry C. Wallace
Department of Geosciences
Building #77
University of Arizona
Tucson, AZ 85721

Dr. William Mortman Mission Research Corporation 735 State Street P.O. Drawer 719 Santa Barbara, CA 93102

U.S. GOVERNMENT AGENCIES

Mr. Alfred Lieberman ACDA/VI-OA, Room 5726 320 21st Street, N.W. Washington, DC 20451

Colonel Jerry J. Perrizo
AFOSR/NP, Building 410
Bolling AFB
Washington, DC 20331-6448

Dr. Robert Blandford AFTAC/CSS 1300 No. 17th St., Suite 1450 Arlington, VA 22209

AFTAC/CA (STINFO) Patrick AFB, FL 32925-6001 Dr. Frank F. Pilotte HQ AFTAC/TT Patrick AFB, FL 32925-6001

Katie Poley CIA-ACIS/TMC Room 4X16NHB Washington, DC 20505

Dr. Larry Turnbull CIA-OSWR/NED Washington, DC 20505

Dr. Ralph W. Alewine, III Dr. Alan S. Ryall, Jr. Ms. Ann U. Kerr DARPA/NMRO 1400 Wilson Blvd. Arlington, VA 22209-2308

> DARPA/OASB/Librarian 1400 Wilson Blvd. Arlington, VA 22209-2308

Dr. Dale Glover
DIA/DT-1B
Washington, DC 20301

Dr. Michael Shore Defense Nuclear Agency/SPSS 6801 Telegraph Road Alexandria, VA 22310

Dr. Max Koontz U.S. Dept of Energy/DP-5 Forrestal Building 1000 Independence Avenue Washington, DC 20585

Defense Technical Information Center Cameron Station Alexandria, VA 22314 (2 copies)

Dr. John J. Cipar, PL/Lw Phillips Lab/Geophysics Directorate Hanscom AFB, MA 01731 James F. Lewkowicz, PL/LW Phillips Lab/Geophysics Directorate Hanscom AFB, MA 01731

Phillips Laboratory (PL/XO) Hansoom AFB, MA 01731

Dr. James Hannon Lawrence Livermore National Laboratory P.O. Box 808 Livermore, CA 94550 (2 copies)

Office of the Secretary of Defense DDR&E Washington, DC 20330

Dr. William Leith U.S. Geological Survey Mail Stop 928 Reston, VA 22092

Dr. Robert Masse Box 25046, Mail Stop 967 Denver Federal Center Denver, CO 80225

Dr. Robert Reinke WL/NTESG Kirtland AFB, NM 87117-6008

CORL MAILING LIST-NM

ORGANIZATION	NAME	NO. COPIES
NON-GOVERNMENT CONTRACTORS		
CALTECH	AHRENS	1
SAIC, SAN DIEGO	BACHE, SEPRENO	2
CANADA, GEOL SURVEY	BASHAM	1
ENSCO, SPRINGFIELD, VA	BAUMGARDT/DER	1
UCSO	BERGER	1
VPI	BOLLNOER	1
SAIC, ROSSLYN	BRATT, CARTER LIBRARIAN	
TELEDYNE GARLAND, TX	BROWNE	1
WOODWARD-CLYDE	BURDICK	1
SHI	CHEFRY	1
U, TORONTO	CHUN	1
ua.a	DAVIS	1
SAN DIEGO STATE U.	DAY	1
SWEDEN, NAT, DEF, RES, INST.	EVA JOHANINISSON	1
MRC, SANTA BARBARA	FISK	1
UCSC	FLATTE	1
PSR	FRITZEL	1
GERMANY, RUHRU	HARJES	1
CALTECH	HELMBERGER	1
SMUGEOPHY8. LAB	HERRIN, STUMP	1
CORNELL	ISACKS, BARAZANGI	1
uas	JOHNSON, MCEVILLY	1
ENSCO, MELBOURNE, PL	KEMERAIT	1.
ANU	KENNETT	1
LINCOUN LAB	LACOSS	1
U, EL	LAMB	1
PENN STATE U.	LANGSTON	1
ucsc	LAY, SCHWARTZ	1
ltxxx	LERNER-LAMPICHAROS	1
GEFNANY, FED INST	MANFRED HENGER	1
AWRE	MARSHALL	1
NER	MARTIN	1
FRANCE, RADIOMANA	MASSINON, MECHELER	2
SMU/PHYSICS DEPT	MCCARTOR, GRAY	1
8-CUBED, LA JOLLA	MCLAUGHLIN	1
UC80	MINSTER, ORCUTT, GIVEN	2
ST LOUIS U	MITCHBL HERPMANN	1
S-CUBED, RESTON	MURPHY	2
RADOX	PULLI	1
NORWAY, NTHE	MINGDAL	2
TELEDYNE, ALEXANDRIA, VA	RIVERS	2
TASC	SAILOR	1

CORL MAILING LIST-NM

ORGANIZATION	NAME	NO. COPIES
usc	SAMMIS, AKI	1
IRIS	SIMPSON	2
U, WASHINGTON	SMITH	1
U, WISCONSIN	THURBER, MEYER	1
МП	TOK90Z/DANTY	1
U. AZ	WALLACE	1
MRC, NEWINGTON, VA	WORTHAN	1
US GOVERNMENT AGENCIES		
ACDA	LIEBERMAN	
APOSPANP	JETRY PETRIZO	1.
AFTAC, CSS, ROSSLYN, YA	BLANDRORD	1
AFTAC/CA	STINPO	1
AFTAC/TT	PLOTTE	1
CIA/ACIS	KATTE POLEY	1
CIAOSWR	TURNBULL	1
DAPPA	ALEWINE, RYALL, KERR	7
DARPARMO	LIBRARIAN	1
DIA	GLOVER	1
DNA/8P68	SHORE	1
DOE	KOONIZ	1
σπο	INFO CTR	
GLYMH	CIPAR	1
GLAWH	LEWKOWICZ	1
GL/XO	×	1
LLNL	HANNON	2
ලන	COPIE	1
SANDIA	CHABL	1
USG6	LETH	1
rscs	MASSE	1
W.MTE9G	PENKE	1
TOTAL NUMBER OF REPORTS		88